

**CHARACTER:**

**1.Physical performance**

- a、Excellent mechanical properties
- b、Excellent thermal stability
- c、Low temperature soft good performance
- d、Good flame retardancy
- e、Of high resistance to chemicals
- f、Chemistry stability is good
- b、Good resistance to high temperature of the engine fluid
- j、Excellent resistance to impact ability

**2.Electrical Properties**

- a、Electrical insulation good
- b、Good the dielectric properties

**3.Processing properties**

- a、Using the hot extrusion processing
- b、Can be twisted pair and multi-core
- c、Good processing properties Harness
- d、Harness processing process good compatibility
- e、According to UL standard design

**4.Environmental protection**

- a、ROHS/REACH compliant


**SHOULD BE USED:**

General commercial, electronic electric appliance and equipment instrument internal connections。

**REFERENCE:**

UL758-2010、UL1581-2009

**Outline:**



**Wire structure description:**

Conductor: Tinned /Bare copper ;  
Insulation materials: PVC Insulation

Appliances with internal , No more than 80 °C temperature of conductor occasion  
Rated temperature: 80°C Rated voltage:300V

STYLE	SIZE AWG	Conductor construction (No./ mm) ±0.005	Conductor resistance 20°C (Ω/Km)	Conductor diameter (mm)	insulation thickness (mm)		Over diameter (mm)	
					Nom.	Min.	Nom.	Tole.
1095	16	26/0.254	14.60	1.50	0.35	0.32	2.20	±0.1
	18	16/0.254	23.20	1.17	0.35	0.32	1.83	±0.1
	20	21/0.18	36.70	0.95	0.35	0.32	1.60	±0.1
	22	17/0.16	59.40	0.76	0.35	0.32	1.44	±0.1
	24	11/0.16	94.20	0.61	0.30	0.24	1.21	±0.1
	26	7/0.16	150.00	0.48	0.30	0.24	1.08	±0.1
	28	7/0.127	239.00	0.38	0.30	0.24	0.98	±0.1
	30	7/0.10	361.00	0.31	0.30	0.24	0.91	±0.1

Stranded conductor single diameter tolerances ±0.005mm;  
Solid conductor diameter tolerances ±0.01mm.

**Marking:** E211048 AWM STYLE 1095 NO.AWG 80°C 300V VW-1 PVC QIFURUI  
 AWM I A 80°C 300V FT1 -LF-  
 OR : E211048 AWM STYLE 1095 NO. AWG 80 °C 300V VW-1 PVC QIFURUI  
 221756 CSA AWM I A 80°C 300V FT1 -LF-

**SAE COLOR SERIES**

* STOCK COLOR CHART				
00-BLACK	01-WHITE	02-RED	03-YELLOW	04-GREEN
05-BLUE	06-BROWN	07-GREY	08-ORANGE	09- VIOLET

**PACKAGE**

*PACKAGE				
Part No.	Packing- Ft/roll			
16AWG	<input type="checkbox"/> 500Ft	<input checked="" type="checkbox"/> 1000Ft	<input type="checkbox"/> 2000Ft	
18-30AWG	<input type="checkbox"/> 500Ft	<input type="checkbox"/> 1000Ft	<input checked="" type="checkbox"/> 2000Ft	

According to customer requirements for packaging packaging